

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE SOUTH BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS

23, 26, 27, 33, AND 34,

IN

TOWNSHIP 32 SOUTH RANGE 6 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated **July 2, 2003**, approved **July 2, 2003**,
which provided for the surveys included under Group Number **959**, and
assignment instructions dated **July 2, 2003**

Survey commenced **May 26, 2004**
Survey completed **July 29, 2004**

INDEX DIAGRAM

Township 32 South, Range 6 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	14 13 23 8	24
30	29	28	18 17 27 10	12 26 6	25
31	32	19 19 33 4	16 14 34 3	10 9 35	36

The Subdivision of Section 23.....Page 20
The Subdivision of Section 26.....Page 21
The Subdivision of Section 27.....Page 23
The Subdivision of Section 33.....Page 26
The Subdivision of Section 34.....Page 27

TOWNSHIP 32 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of sections 23, 26, 27, 33, and 34, in T. 32 S., R. 6 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
All	A.J. Stewart Jr.	1873	
Portion		J.R. and Quimby Stewart	1910
Portion		R. Gentry	1920
Portion		C.J. Terry and R. Gentry	1920
EAST BOUNDARY			
Portion	A.J. Stewart Jr.	1873	
Portion	J.R. and Quinby Stewart	1910	
Portion		R. Gentry	1920
Portion		C.J. Terry and R. Gentry	1920
Portion		W.H. Sylvester	1960
WEST BOUNDARY			
All	A.J. Stewart Jr.	1873	
All		J.R. and Quinby Stewart	1910
NORTH BOUNDARY			
All	A.J. Stewart Jr.	1873	
All		J.R. and Quinby Stewart	1910
SUBDIVISION			
Portion	A.J. Stewart Jr.	1873	
Portion	J.R. and Quinby Stewart	1910	J.R. and Quinby Stewart 1910

A survey was executed by Neil Rhodes of Bulloch Brothers Engineering in 1977, with plat dated 12/6/77.

T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 959, dated July 2, 2003.

The direction of the lines were determined by references to true meridians, established by the Global Positioning System (GPS) utilizing Real-time kinematic (RTK) techniques throughout the survey. Trimble Model 5700 global positioning system receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from National Geodetic Survey Station "EXTRA", with published data as follows:

Latitude: 38°00'25.30326" N. Longitude: 112°30'57.87475" W.
NAD 1983 (1994). Elevation 7114 Ft., N.A.V.D. 1988

The geographic position of the corner of sections 34 and 35 only, on the South Boundary of T. 32 S., R. 6 W., as determined by a tie made to National Geodetic Survey Station "EXTRA" is as follows:

Latitude: 37°58'12.654" N. Longitude: 112°30'57.065" W.
NAD 1983.

NOTE: Isolated throughout the project area, some large discrepancies were found between record positions and found locations of the original 1873 bearing trees. For further detail, see the field note record.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.J. Stewart Jr. in
1873, and the Resurvey by R. Gentry in 1920.

Beginning at the corner of sections of 34 and 35 only, on the
south boundary of the township, monumented with a sandstone
18x8x4, inches loosely set in a mound of stone, plainly marked
with 2 notches on the east and 4 notches on the west edges.

from which

A juniper 16 ins. diam., with scribe marks visible on a
partially healed blaze bears, N. 70° W., 82.5 links
distance.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24
inches in the ground, with the aluminum cap marked:

T32SR6W
S34|S35
T33SR6W
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the
base of the aluminum post.

Raised a mound of stone, 4 ft. by 2 ft. base by 1 ft. high,
north of the aluminum post.

The corner is located on a steep rocky northwest slope in
pinyon, juniper and oak, 60 ft. north of a fence line
projecting east and west.

S. 88° 43.0' W., on the south boundary of the township.

31.476

The corner of sections 3 and 4 only, monumented with an iron
post, 1 inch diameter firmly set in a small mound of stone,
with the brass cap marked 1/4 S 3, S 4, 1920. I remove the 1/4
mark and added the date 2004 to the brass cap to now read:

S4|S3
T33SR6W
2004
1920

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located 14 ft. north of a fence, projecting east and west.

N. 88° 13.6' W., beginning new measurement.

- 9.091** The 1/4 section corner of section 34 only, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, with the brass cap marked as described in the official record of the resurvey executed by R. Gentry in 1920.

Corner is located on top of a rocky spur bearing northeast in pinyon and juniper with sagebrush undergrowth.

S. 88° 55.5' W., beginning new measurement.

- 20.230** Point for the W 1/16 section corner of section 34 only, not monumented.

- 30.818** The 1/4 section corner of section 4 only, monumented with an iron post 1 inch diameter, firmly set in a mound of stone, with the brass cap marked as described in the official record of the resurvey executed by R. Gentry in 1920.

Corner is located on top of a small spur ridge bearing northeast and southwest, in pinyon and juniper with sagebrush undergrowth.

S. 89° 43.8' W., beginning new measurement.

- 9.642** The corner of sections 33 and 34 only, monumented with a sandstone, 18x7x4 inches, loosely set, plainly marked with 3 notches on the east and west edges.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground with the brass cap marked:

T32SR6W
S33|S34
T33SR6W
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 3 ft. by 2 ft. base by 1 ft. high, north of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on top of a finger ridge bearing, N. 58° W.,
S. 58° E.

N. 89° 26.9' W., continuing on the south boundary of the
township.

30.282

The corner of sections 4 and 5 only, monumented with an iron
post, 2 inches diameter, firmly set in a mound of stone, with
the brass cap marked as described in the official record of
the resurvey executed by R. Gentry in 1920.

The corner is located on flat rocky ground, 10 feet north of a
fence line projecting east and west.

N. 89° 52.0' W., beginning new measurement.

10.392

The 1/4 section corner of section 33 only, monumented with a
sandstone 24x14x4 inches, loosely set in a mound of stone, and
plainly marked 1/4 on the north face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24
inches in the ground, with the aluminum cap marked:

T32SR6W
1/4 S33
T33SR6W
2004

Deposited the marked stone in a mound of stone 3 ft. by 2 ft.
base by 1 ft. high, north of the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the
base of the aluminum post.

Corner is located on a moderate north slope, 9 ft. north of a
fence line projecting east and west.

N. 89° 48.3' W., beginning new measurement.

29.476

The 1/4 section corner of section 5 only, monumented with an
iron post, 1 inch diameter, firmly set in a mound of stone,
with the brass cap marked as described in the official record
of the resurvey executed by R. Gentry in 1920.

Corner is located 3 ft. north of a fence line projecting east
and west.

N. 89° 45.8' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS
10.584

The corner of sections 32 and 33 only, monumented with an iron post, 3 inches diameter, firmly set projecting 12 inches above the ground, with the brass cap marked as described in the official record of the resurvey executed by J.R. and Quinby Stewart in 1910.

A cedar post with a forest service boundary sign is located alongside the iron post.

Corner is located 2.5 ft. north of a fence, projecting east and west.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873.

From the corner of sections 25, 26, 35, and 36, monumented with an Iron County Survey monument, an aluminum post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, with the aluminum cap marked, 25 in the NE quadrant, 36 BB LS 4100 in the SE quadrant, 35 1977 in the SW quadrant, and 26 in the NW quadrant.

From which

A juniper 20 ins. diam., with faint scribe marks visible on open blaze bears, S. 32° E., 51 links.
(Record S. 65° E., 50 links.)

A juniper 20 ins. diam., with no blaze or scribe marks visible on the tree, bears, S. 71° E., 40 links distance.
(Record N. 65° E., 40 links.)

The bearing, S. 71° E. and the distance 40 links to the bearing tree as shown above was determined from the field note record and associated coordinates obtained from Neil (Bud) Rhodes of Bulloch Brothers Engineering. The tree was inadvertently not tied in during the course of this survey.

Bulloch Brothers Engineering determined the position for the corner of sections 25, 26, 35 and 36 at a mathematical intersection using record distances from the two found trees. Note: Isolated throughout the project area, some large discrepancies were found between record positions and found locations of the original 1873 bearing trees.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The trees are accepted as the original NE and SE bearing trees of the survey executed by A. J. Stewert Jr. in 1873. No remaining evidence of the original marked stone, or other bearing trees were found during the course of this survey.

Due to the evidence supporting the findings that Bulloch Brothers Engineering used an acceptable procedure to reestablish this corner, and because of the lack of any additional evidence of the original section corner position, I accept the monument as set by Bulloch Brothers Engineering in 1977, as the best available evidence of the position of the original section corner.

Corner is located on a steep southeast slope in old pinyon and juniper growth.

N. 1° 11.4' E., between sections 25 and 26.

40.152

The 1/4 section corner of sections 25 and 26, monumented with a granite stone 14x10x6 inches, loosely set, and plainly marked 1/4 on the west face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground with the aluminum cap marked:

T32SR6W
1/4
S26|S25
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 3 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Corner is located on a moderate rocky northwest slope in juniper and pinyon growth.

N. 0° 35.2' E., beginning new measurement.

40.348

The corner of sections 23, 24, 25, and 26, monumented with an iron post 2 inches diameter, firmly set in a mound of stone, with the brass cap marked as described in the official record of the resurvey executed by J.R. and Quinby Stewart in 1910.

from which

A pinyon 22 ins. diam., with no visible scribe marks on a healed blaze bears, N. 68° E., 62.5 links distance.
(Record N. 20° E., 70 links)

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A pinyon 18 ins. diam., with no visible scribe marks on a healed blaze bears, S. 18° E., 12 links distance.
(Record S. 5° E.)

A juniper 12 ins. diam., with scribe marks visible on a partially healed blaze bears, N. 89° W., 50.5 links.
(Record N. 85° W., 28 links)

Corner is located on a gradual southeast slope in pinyon and juniper growth.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873, and the Retracement Executed by
J.R. and Quinby Stewart in 1910.

N. 0° 05.5' W., between sections 23 and 24.

40.132

The 1/4 section corner of sections 23 and 24, monumented with a scattered mound of stone, no remaining evidence of the marked stone or iron post was found. This mound of stone is accepted as the best available evidence of the position of the 1/4 section corner.

from which

A juniper, 24 ins. diam., scribed 1/4 S24 BT, on a partially healed blaze bears, S. 11° E., 148 links distance. (Record S. 9° E.)

At the center of the mound of stone

Set an aluminum post 30 inches long, 2 1/2 diameter, 24 inches in the ground with the aluminum cap marked:

T32SR6W
1/4
S23|S24
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 2 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Corner is located on a moderate north facing slope, 24 ft. south of a drainage 7 ft. wide, draining west.

N. 0° 56.9' W., beginning new measurement.

40.455

The corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 3 ft. base by 1 ft. high, with the brass cap marked as

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

described in the official record of the retracement executed by J.R. and Quinby Stewart in 1910.

Corner is located on a moderate south slope in sagebrush.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873.

From the corner of sections 34 and 35 only, on the south boundary of the township, hereinbefore described.

N. 0° 57.2' E., between sections 34 and 35.

- 40.436** Point for the 1/4 section corner of sections 34 and 35, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone 4 ft. by 3 ft. base, by 1 ft. high to the top of the aluminum cap marked:

T32SR6W
1/4
S34|S35
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a moderate rocky west facing slope in pinyon and juniper growth.

- 80.872** The corner of sections 26, 27, 34, and 35, monumented with a granite stone, 22x7x4 inches, firmly set in a small mound of stone, plainly marked with 1 notch on the south and 2 notches on the east edges.

from which

A pinyon 10 ins. diam., down and dead with scribe marks visible on a partially healed blaze bears, N. 17° W., 72 links distance. (Record N. 15° E., 26 links.)

A juniper 9 ins. diam., with scribe marks visible on an open blaze bears, S. 45° E., 18.5 links distance. (record 20 links)

A pinyon 12 ins. diam., down and dead with no visible scribe marks on an open blaze, not remeasured. This tree was determined to be the northwest bearing tree.

No remaining evidence of the southwest bearing tree was found.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground in a mound of stone, 4 ft. by 4 ft. base, to the top of the aluminum cap marked:

T32SR6W
S27|S26
S34|S35
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a moderate rocky southwest slope in dense pinyon and juniper growth.

From the corner of sections 25, 26, 35, and 36.

N. 89° 11.5' W., between sections 26 and 35.

39.756

Point for the 1/4 section corner of sections 26 and 35, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, in a mound of stone, 4 ft. by 4 ft. base, to the top of the aluminum cap marked:

T32SR6W
S26
1/4 —
S35
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a steep rocky southeast slope in mature juniper and pinyon growth.

79.512

The corner of sections 26, 27, 34, and 35.

N. 0° 05.2' E., between sections 26 and 27.

20.163

Point for the S 1/16 section corner of sections 26 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, on solid rock, in a mound of stone, 5 ft. base to the top of the aluminum cap marked:

S 1/16
S27|S26
2004

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a steep rocky southwest slope in boulders.

From this corner, the corner of fences, projecting north and west, bears N. 23° 10' E., 118 feet distance.

- 40.326** The 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 inch diameter, firmly set, projecting 20 inches above the ground, in a mound of stone, 3 ft. base to a point 8 inches below the top of the brass cap marked 1/4 S26 S27 1910.

from which

A pinyon 16 ins. diam., dead and standing, with scribe marks visible on a partially healed blaze bears, S. 50° W., 77.5 links distance. (Record S. 62 1/2° W., 76 links).

No remaining evidence of the NE bearing tree was found.

No record of the retracement of this line or the monumentation of this point was found in the field note record of the retracement executed by J.R. and Quinby Stewart in 1910.

Alongside the iron post, found a granite stone, 22x14x10 inches, dimly marked 1/4.

The iron post monument is accepted as the best available evidence of the position of the original marked stone.

Corner is located 2.5 ft. east of the corner of fences projecting north, south, and west, on a steep and rocky northwest slope.

N. 0° 17.5' E., beginning new measurement.

- 19.931** Point for the N 1/16 section corner of sections 26 and 27, not monumented.

- 39.862** The corner of sections 22, 23, 26, and 27, at the intersection of fences, projecting north, south, east, and west.

The intersection of fences is accepted as the best available evidence of the position of the original section corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground with the aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T32SR6W

S22	S23
-----	-----

S27	S26
-----	-----

2004

From this corner, west 66 ft. distance found a granite stone 16x8x7 inches, lying loose in a fence line projecting west, plainly marked with 2 notches on one side and 2 notches on another. Deposited the marked stone alongside the aluminum post.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873, and the Retracement Executed by
JR. and Quinby Stewart in 1910.

From the corner of sections 23, 24, 25, and 26.

N. 89° 40.9' W., between sections 23 and 26.

39.854

The 1/4 section corner of sections 23 and 26, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone 4 ft. base to top of the brass cap marked as described in the official record of the retracement executed by J.R. and Quimby Stewart in 1910.

from which

A pinyon 24 ins. diam., with scribe marks 1/4 S23 BT visible on an open blaze bears, N. 23° E., 69 links distance. (Record N 10° E., 82 links).

A juniper 24 ins. diam., with scribe marks 1/4 S26 BT visible on a partially healed blaze bears, S. 18° E., 35.5 links distance. (This bearing tree is not of record).

Corner is located on a steep rocky west slope in scattered pinyon and juniper growth.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873.

N. 89° 09.2' W., beginning new measurement.

20.312

Point for the W 1/16 section corner of sections 23 and 26, not monumented.

40.624

The corner of sections 22, 23, 26 and 27.

N. 0° 24.1' W., between sections 22 and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.275** The 1/4 section corner of sections 22 and 23, monumented with a granite stone, 14x8x5 inches, firmly set, plainly marked 1/4 on the west face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W

1/4

S22|S23

2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located at the corner of fences, projecting south, east, and west, near the top of a ridge bearing east and west, in grass and scattered sagebrush.

From this corner, National Geodetic Survey Station "Extra", monumented with a standard brass tablet, stamped EXTRA 1938, bears, N. 48° 22' 22" W., 3.087 chains distance.

N. 0° 25.8' W., beginning new measurement.

- 40.036** The corner of sections 14, 15, 22, and 23, monumented with a granite stone 18x18x5 inches, firmly set in a mound of stone, plainly marked with 3 notches on the east and 2 grooves on the north edges. (Record 3 notches on the south and 2 notches on the east edges).

At the corner point

Set a stainless steel post 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 3 ft. base to top of the brass cap marked:

T32SR6W

S15|S14

S22|S23

2004

Deposited the marked stone alongside the stainless steel post.

Deposited a magnet enclosed in a clear plastic case at the base of the stainless steel post.

Corner is located on flat ground on top of a low ridge in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 13, 14, 23, and 24.

S. 89° 45.6' W., between sections 14 and 23.

- 40.311** The 1/4 section corner of sections 14 and 23, monumented with a granite stone 16x8x4 inches, firmly set, plainly marked 1/4 on the south face, with a scattered mound of stone to the north. (Record 1/4 marked on the north side)

At the corner point

Set a stainless steel post 30 inches long, 2 1/2 inches diameter 24 inches in the ground, with the brass cap marked:

T32SR6W
S14
1/4 —
S23
2004

Deposited the marked stone alongside the stainless steel post.

Deposited a magnet enclosed in a clear plastic case at the base of the stainless steel post.

Raised a mound of stone, 4 ft. by 3 ft. base by 2 ft. high, north of the stainless steel post.

Corner is located on flat ground in sagebrush.

N. 88° 58.3' W., beginning new measurement.

- 40.001** The corner of sections 14, 15, 22, and 23.

From the corner of sections 33 and 34 only, on the south boundary of the township, hereinbefore described.

N. 0° 41.3' E., between sections 33 and 34.

- 20.310** Point for the S 1/16 section corner of sections 33 and 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

S 1/16
S33|S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raised a small mound of stone to the west of the aluminum post.

Corner is located on a gradual northeast slope in grass and sagebrush, 1.5 ft. north of a fence line, projecting east and west.

- 40.620** Point for the 1/4 section corner of sections 33 and 34, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
1/4
S33|S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 2 ft. by 2 ft. base, by 1 ft. high, west of the aluminum post.

Corner is located on a gradual west slope in grass and sagebrush, in an old chaining.

- 60.930** Point for the N 1/16 section corner of sections 33 and 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the brass cap marked:

N 1/16
S33|S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone 2 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in silty soil on a gradual northwest slope, in sagebrush and rabbit brush, 95 ft. east of a dirt road, 10 ft. wide bears, N. 35° W., and S. 35° W.

- 81.240** Point for the corner of sections 27, 28, 33 and 34, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T32SR6W
S28|S27
S33|S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in a fence, projecting east and west, in rabbit brush.

From the corner of sections 26, 27, 34, and 35.

N. 89° 48.1' W., between sections 27 and 34.

40.730

The 1/4 section corner of sections 27 and 34, monumented with a limestone 18x10x4 inches, lying loose in a scattered mound of stone, dimly marked 1/4.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
S27
1/4 —
S34
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone to the north of the aluminum post.

Corner is located on flat ground in sagebrush.

S. 88° 50.8' W., beginning new measurement.

20.320

Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

S27
W 1/16 —
S34
2004

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on flat ground in sagebrush.

From this corner, the corner of fences, projecting north, south and west, bears S. 64° W., 50 feet distance.

40.640 The corner of sections 27, 28, 33 and 34.

N. 0° 06.2' E., between sections 27 and 28.

20.308 Point for the S 1/16 section corner of sections 27 and 28, not monumented.

40.616 The 1/4 section corner of sections 27 and 28, monumented with a granite stone, 16x8x5 inches, loosely set, in a scattered mound of stone, dimly marked 1/4, on the west face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone 4 ft. base to the top of the aluminum cap marked:

T32SR6W
1/4
S28|S27
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located in a fence, projecting east and west on the top of a low ridge, on a gradual east slope in sagebrush.

N. 0° 18.9' E., beginning new measurement.

20.200 Point for the N 1/16 section corner of sections 27 and 28, not monumented.

40.400 The corner of sections 21, 22, 27 and 28, monumented with a iron post, 2 inches diameter, firmly set, projecting 16 inches above a mound of stone, with the brass cap marked as described in the official record of the retracement executed by J.R. and Quinby Stewart in 1910.

Corner is located on a gradual southwest slope in grass and sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 22, 23, 26, and 27.

N. 89° 50.4' W., between sections 22 and 27.

40.666

The 1/4 section corner of sections 22 and 27, monumented with a limestone, 18x7x7 inches, plainly marked 1/4, on the north face.

At the corner point

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
S22
1/4 —
S27
2004

Deposited the marked stone alongside the aluminum post.

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone, west of the aluminum post.

Corner is located on flat open ground, at the corner of fences projecting south, east and N 20° W.

N. 89° 56.9' W., beginning new measurement.

20.324

Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

S22
W 1/16 —
S27
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in the bottom of a small swell runs east and west in an old chaining.

40.648

The corner of sections 21, 22, 27, and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873, and the Retracement Executed by
JR. and Quinby Stewart in 1910.

From the corner of sections 32 and 33 only, on the south
boundary of the township, hereinbefore described.

N. 0° 05.1' W., between sections 32 and 33.

- 40.086** The 1/4 section corner of sections 32 and 33, monumented with
an iron post 1 inch diameter, firmly set, projecting 8 inches
above ground, with the brass cap marked as described in the
official record of the retracement executed by J.R. and Quinby
Stewart in 1910.

Corner is located on flat ground in sagebrush.

N. 0° 03.5' E., beginning new measurement.

- 41.186** The corner of sections 28, 29, 32, and 33, monumented with an
iron post 2 inches diameter, loosely set, in a small mound of
stone, with the brass cap marked as described in the official
record of the retracement executed by J.R. and Quinby Stewart
in 1910.

Raised a mound of stone, 5 ft. by 3 ft. base by 2 ft. high,
around the iron post.

Corner is located on steep rocky southeast slope.

Reestablishment of the Survey Executed by
A.J. Stewart Jr. in 1873.

From the corner of sections 27, 28, 33, and 34.

N. 89° 39.0' W., between sections 28 and 33.

- 40.855** Point for the 1/4 section corner of sections 28 and 33, at
proportionate distance. No remaining evidence of the original
corner was found.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24
inches in the ground, with the aluminum cap marked:

T32SR6W
S28
1/4 ———
S33
2004

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raise a small mound of stone, north of the aluminum post.

Corner is located 18 feet north of a fence, projecting east and west, on flat ground in sagebrush.

From this corner, the corner of fences, projecting south, east and N. 40° W., bears S. 68° W., 47.5 feet distance.

81.710 The corner of sections 28, 29, 32, and 33.

The Subdivision of Section 23,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. 0° 51.4' W., on the N - S centerline of section 23.

40.398 Point for the center 1/4 section corner at intersection with the E - W centerline of section 23.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
C 1/4
S23
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 2 ft. by 2 ft. base, by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on a gradual west slope in sagebrush.

80.200 The 1/4 section corner of sections 14 and 23.

From the 1/4 section corner of sections 23 and 24.

N. 89° 18.9' W., on the E - W centerline of section 23.

40.392 The center 1/4 section corner of section 23.

80.688 The 1/4 section corner of sections 22 and 23.

THE SUBDIVISION OF SECTION 26,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 26,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 0° 48.8' E., on the N - S centerline of section 26.

- 40.237** Point for the center 1/4 section corner at intersection with the E - W centerline of section 26.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, over a cross "X", chiseled on solid rock, in a mound of stone, 5 ft. by 4 ft. base to the top of the aluminum cap marked:

T32SR6W
C 1/4
S26
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a steep north facing slope in pinyon and juniper with sagebrush undergrowth.

- 60.197** Point for the center N 1/16 section corner of section 26.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
N 1/16 | S26
C
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located east of highway 20 on a steep northwest slope in tall sagebrush.

- 80.157** The 1/4 section corner of sections 23 and 26.
-

From the 1/4 section corner of sections 25 and 26.

N. 89° 04.1' W., on the E - W centerline of section 26.

- 40.016** The center 1/4 section corner of section 26.

THE SUBDIVISION OF SECTION 26,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

60.148

Point for the center W 1/16 section corner of section 26.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

W 1/16
C — C
S26
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone, north of the aluminum post.

Corner is located on a moderate rocky west slope in juniper and sagebrush undergrowth, 130 feet west of the top of a ridge bearing north and south.

From this corner, S. 70° E., 54 feet distance, found a mound of stone, 2 ft. by 2 ft. base, by 1 ft. high.

80.280

The 1/4 section corner of sections 26 and 27.

From the center W 1/16 section corner of section 26.

N. 0° 33.2' E., on the N - S centerline of the NW 1/4 of section 26.

19.945

Point for the NW 1/16 section corner at intersection with the E - W centerline of the NW 1/4 of section 26.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

NW 1/16
S26
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 2 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on a moderate north slope near toe of slope in sagebrush.

From this corner, the corner of fences, projecting north, south and west, bears N. 52° E., 29 feet distance.

39.890

The point for the W 1/16 section corner of sections 23 and 26.

THE SUBDIVISION OF SECTION 26,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 section corner of section 26.

N. 89° 06.7' W., on the E - W center line of the NW 1/4 of section 26.

20.222 The NW 1/16 section corner of section 26.

40.444 The point for the N 1/16 section corner of sections 26 and 27.

The Subdivision of Section 27,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. 0° 13.7' E., on the N - S centerline of section 27.

19.996 Point for the center S 1/16 section corner of section 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
S 1/16 | S27
C
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone, west of the aluminum post.

Corner is located on flat ground on top of a low ridge in sagebrush, S. 20° W., 4.5 feet from the corner of fences, projecting north, east and west.

39.992 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
C 1/4
S27
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

THE SUBDIVISION OF SECTION 27,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in pasture ground, S. 70° W., 2.2 feet distance from the corner of fences, projecting east, west and north.

60.077 Point for the center N 1/16 section corner of section 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
N 1/16 | S27
C
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located at the corner of old fences projecting north, east and west, in rabbit brush.

80.162 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

S. 89° 43.6' W., on the E - W centerline of section 27.

40.627 The center 1/4 section corner of section 27.

60.984 Point for the center W 1/16 section corner of section 27, not monumented.

81.341 The 1/4 section corner of sections 27 and 28.

From the S 1/16 section corner of sections 26 and 27.

S. 89° 57.8' W., on the E - W centerline of the SE 1/4 of section 27.

40.678 The center S 1/16 section corner of section 27.

From the W 1/16 section corner of sections 27 and 34.

N. 0° 09.9' E., on the N - S centerline of the SW 1/4 of section 27.

20.152 Point for the SW 1/16 section corner at intersection with the E - W centerline of the SW 1/4 of section 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

THE SUBDIVISION OF SECTION 27,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

SW 1/16
S27
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone, 2 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on flat ground in sagebrush.

From this corner, the corner point of the extension of a fence line from the south, and a fence to the east, bears S. 13° W., 30 feet distance.

40.304 The point for the center W 1/16 section corner of section 27.

From the center S 1/16 section corner of section 27.

S. 89° 17.3' W., on the E - W centerline of the SW 1/4 of section 27.

20.338 The SW 1/16 section corner of section 27.

40.676 The point for the S 1/16 section corner of sections 27 and 28.

From the point for the center W 1/16 section corner of section 27.

N. 0° 16.3' E., on the N - S centerline of the NW 1/4 of section 27.

20.142 Point for the NW 1/16 section corner at intersection with the E - W centerline of the NW 1/4 of section 27.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

NW 1/16
S27
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a small mound of stone, west of the aluminum post.

Corner is located on flat ground in sagebrush.

40.284 The W 1/16 section corner of sections 22 and 27.

THE SUBDIVISION OF SECTION 27,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 section corner of section 27.

S. 89° 53.4' W., on the E - W centerline of the NW 1/4 of section 27.

20.341 The NW 1/16 section corner of section 27.

40.682 The point for the N 1/16 section corner of sections 27 and 28.

The Subdivision of Section 33,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of section 33 only, on the south boundary of the township, hereinbefore described.

N. 0° 33.3' E., on the N - S centerline of section 33.

20.134 Point for the center S 1/16 section corner of section 33.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

C
S 1/16 | S33
C
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post

Corner is located on flat ground, 11 feet, at S. 65° W., from the corner of fences, projecting north and east.

40.268 Point for the center 1/4 section corner at intersection with the E - W centerline of section 33.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
C 1/4
S33
2004

Deposited a magnet enclosed in a clear plastic base at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on flat ground in sagebrush, 19 ft. east of a fence, projecting north and south.

81.171 The 1/4 section corner of sections 28 and 33.

THE SUBDIVISION OF SECTION 33,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 33 and 34.

S. 89° 57.0' W., on the E - W centerline of section 33.

40.767 The center 1/4 section corner of section 33.

81.272 The 1/4 section corner of sections 32 and 33.

From the S 1/16 section corner of sections 33 and 34.

N. 89° 48.2' W., on the E - W centerline of the SE 1/4 of section 33.

40.720 The center S 1/16 section corner of section 33.

The Subdivision of Section 34,
T. 32 S., R. 6 W., Salt Lake Meridian, Utah

From the 1/4 section corner of section 34 only, on the south boundary of the township, hereinbefore described.

N. 0° 49.0' E., on the N - S centerline of section 34.

20.214 Point for the center S 1/16 section corner of section 34, not monumented.

40.428 Point for the center 1/4 section corner at intersection with the E - W centerline of section 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

T32SR6W
C 1/4
S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a gradual northwest slope in sagebrush.

60.932 Point for the center N 1/16 section corner of section 34, not monumented.

81.436 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

S. 89° 23.5' W., on the E - W centerline of section 34.

THE SUBDIVISION OF SECTION 34,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.649

The center 1/4 section corner of section 34.

60.920

Point for the center W 1/16 section corner of section 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground with the aluminum cap marked:

W 1/16
C — C
S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Raised a mound of stone 3 ft. by 2 ft. base by 1 ft. high, north of the aluminum post.

Corner is located on a gradual north slope, 20 ft. east of a fence, projecting north and south.

81.191

The 1/4 section corner of sections 33 and 34.

From the point for the W 1/16 section corner of section 34 only, on the south boundary of the township, hereinbefore described.

N. 0° 45.1' E., on the N - S centerline of the SW 1/4 of section 34.

20.329

Point for the SW 1/16 section corner at intersection with the E - W centerline of the SW 1/4 of section 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, in a mound of stone 4 ft. base by 1 ft. high, with the aluminum cap marked:

SW 1/16
S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Corner is located on a steep rocky west slope, on the southwest side of an active rock quarry.

40.591

The center W 1/16 section corner of section 34.

From the point for the center S 1/16 of section 34.

S. 89° 15.2' W., on the E - W centerline of the SW 1/4 of section 34.

THE SUBDIVISION OF SECTION 34,
T. 32 S., R. 6 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.250 The SW 1/16 section corner of section 34.

40.500 The S 1/16 section corner of sections 33 and 34.

From the center W 1/16 section corner of section 34.

N. 0° 45.2' E., on the N - S centerline of the NW 1/4 of section 34.

20.407 Point for the NW 1/16 section corner at intersection with the E - W centerline of the NW 1/4 of section 34.

Set an aluminum post 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with the aluminum cap marked:

NW 1/16
S34
2004

Deposited a magnet enclosed in a clear plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on flat ground in sagebrush, 33 feet east of a fence, projecting north and south.

40.814 The W 1/16 section corner of sections 27 and 34.

From the point for the center N 1/16 section corner of section 34.

S. 89° 07.1' W., on the E - W centerline of the NW 1/4 of section 34.

20.295 The NW 1/16 section corner of section 34.

40.590 The N 1/16 section corner of sections 33 and 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Name	Capacity
Jeremy Davis Samantha Hamblin	Survey Technician Survey Aid

CERTIFICATE OF SURVEY

I, **Larry V. Judd, Cadastral Surveyor**, hereby certify upon honor, that in pursuance of special instructions bearing the date of the **2nd day of July, 2003**, I have **executed a dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines, and the subdivision of sections 23, 26, 27, 33, and 34, in Township 32 South, Range 6 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/24/2006
Date


(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the **dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of sections 23, 26, 27, 33, and 34, in Township 32 South, Range 6 West, Salt Lake Meridian, Utah,**

executed by **Larry V. Judd, Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

September 13, 2006
Date


(Chief Cadastral Surveyor for Utah)